




# CURVE OFFSET CANTILEVER



## SUGGESTED USES:

- PARKING LOTS
- WALKWAYS
- POOLS
- DECKS
- SPORTS
- BLEACHERS
- PATIOS
- CARWASH
- AND MANY MORE.



In line with our policy of continuous product development, we reserve the right to change models, sizes, specifications and prices without prior notice. All orders placed will be for the currently available specification of the relevant item. Design rights and copyrights apply to all products shown in this product sheet. No part of the publication can be copied or reproduced in any form whatsoever without prior consent of the publisher.

## CONFIGURATION OPTIONS



SINGLE BAY



+1 EXTENSION



MULTIPLE EXTENSIONS

## SPECIFICATIONS

Commercial 95  
**Synthesis** HDPE SHADECLOTH  
Advanced Polymer Fabrics

<b>Base Material:</b>	UV Stabilized High Density Polyethylene
<b>Construction:</b>	Monofilament yarn and tape
<b>Knitt Pattern:</b>	Lock-Stitch
<b>Heat Seat:</b>	
<b>Mass:</b>	10.3 oz/sq.yd
<b>Roll width:</b>	9'10" (3m)
<b>Roll length:</b>	54-1/2 Yds (50m)
<b>Temperature range:</b>	-22 F to + 16 F
<b>% UVR Block:</b>	Up to 95%+
<b>Approximate Cover Factor:</b>	95% plus
<b>Approximate UV Block:</b>	95% plus
<b>Warranty:</b>	10 year UV – Refer to Product Warranty for details
<b>Flammability:</b>	NFPA 701 – 99 Test Method 2 –Pass E-84-Pass Additional Flame Resistant Test/ Data available on request.
<b>Colors:</b>	Aquatic Blue / Brunswick Green / Ochre Red / Natural / Rivergum Green / Steel Grey / Black / Cherry Red / Desert Sand / Navy Blue / Sky Blue / Turquoise / Yellow

PRECONSTRAINT 502  
**Serge Ferrari** PVC MEMBRANE

Technical properties	Preconstraint 502	Standards
Yarn	1100 dtex PES HT	
Weight	17.4 oz/sqyd	EN ISO 2286-2
Width	70.9 inches	
<b>Physical properties</b>		
Tensile strength (warp/weft)	250/250 daN/5 cm	EN ISO 1421
Tear strength (warp/weft)	25/20 daN	DIN 53.363
Adhesion	9/9 daN/5 cm	EN ISO 2411
<b>Surface treatment</b>		
Finish	Varnish both sides	
<b>Flame retardancy</b>		
Rating	M2/NFP 92-507 • B1/DIN 4102-1 • B5 7837 • 1530.3/AS/NZS • SP METHOD 2205 M2/UNE 23.727-90 • VKF 5.3/5N 198898 • Schwerbrennbar Q1-Yr1/ONORM A 3800-1 CLASSE 1/UNI 9177-87 • METHOD 1/NFPA 701 • CSFM T19 • CLASS A/ASTM E84 G1/GOST 30244-94 • CAN ULCS 109	
Euroclass	B-s2,d0/ EN 13501-1	
<b>Management system</b>		
for Quality	ISO 9001	
Color	Upon request	

**TIGER Drylac**  
Powder Coatings STRUCTURE POWDER COAT

11 Colors available (standard)
Tan, Brown, Beige, Green, Orange, Yellow, Blue, Red, Black, White, Grey
Additional RAL colors upon request

**Tenara** SEWING THREAD

Unaffected by sunlight	Colors will not fade
Weather-Proof	CLEAR for optimal fabric blending
Easy to clean	Vibrant fade resistant colors
Specifications upon request	

-This web site contains the "TensoShade" logo, dots Image, & dots logo. Let's Get You Covered, The Leading Source for the Outdoors, and other valuable trademarks and service marks owned and used by TensoShade to distinguish its wares and services. These trademarks and service marks and related proprietary property are protected from copying and simulation under national and international laws and may not be reproduced, copied, or otherwise used without the express prior written permission of TensoShade.  
-Commercial 95 Architectural Shade Fabric, Synthesis Advanced Polymer Fabrics, Coolaroo, and logos are trademarks or registered trademarks of Synthesis in the United States, other countries, or both.  
-Serge Ferrari, Preconstraint Solis Textiles, Preconstraint 502, Ferrari, Ferrari Architecture, and logos are trademarks or registered trademarks of Ferrari Architecture in the United States, and other countries, or both.  
-Tiger Drylac Powder Coatings and logo are trademarks or registered trademarks of Tiger in the United States, and other countries, or both.  
-Tenara Sewing Thread, Gore and logos are trademarks or registered trademarks of Gore in the United States, and other countries, or both.  
-References in this publication to TensoShade products and services do not imply that TensoShade intends to make them available in all countries in which TensoShade operates.



\* 5 years in Cherry Red and Yellow



\* Only in certain sizes

www.TensoShade.com

T. 1.877-378-2828 - T.210.888.0128 - E. Info@TensoShade.com

